

CARING FOR YOUR POWDER-COATED LOUVRE PRODUCTS

To extend the life of powder-coated articles and to comply with warranty requirements for powder-coated aluminium joinery, a simple, regular maintenance program should be implemented. The effects of ultraviolet light, atmospheric pollution, dirt, grime, and airborne salt deposits can all accumulate over time and should be removed at regular intervals. Generally cleaning should take place every six months.

In areas where pollutants are more prevalent, such as beachfront houses and industrial or geothermal areas, then a cleaning program should be carried out on a more frequent basis i.e.; every one to three months.

CLEANING YOUR POWDER COATING

Periodic cleaning is essential to remove dirt, grime, and accumulated salt deposits from both powder-coated and anodised surfaces. Three steps to cleaning your powder coating are:

- 1. Carefully remove any loose surface deposits with a wet sponge.
- 2. Use a soft brush (non-abrasive) and a mild household detergent (do not use solvents) in warm water, to remove dust, salt, and other deposits.
- 3. Rinse off with clean fresh water.









WARRANTY YEARLY LIMITATIONS

For the first two years, all materials and labour shall be covered by this warranty. For the third year, warranty will cover 60% of any material required, excluding the cost of labour, unless the claim relates to workmanship. For the fourth year, 40% of materials shall be covered, excluding labour costs unless the claim relates to workmanship. For the fifth year, 20% of materials shall be covered but not labour unless the claim relates to workmanship. Determination for any warranty claim shall be at the sole discretion of NZ LOUVRES. The warranty details on all Goods supplied by NZ LOUVRES, but not manufactured by NZ LOUVRES is limited to the manufacturer's warranty. Details of such manufacturer's warranties will be provided to the Purchaser upon request.

POWDER COATING

Our standard exterior finishes are from the extensive Dulux Duralloy range unless otherwise stated and offer a variety of hard-wearing thermoset powder coatings with decorative and durability features to provide excellent overall performance. Duralloy is designed to provide outstanding resistance to New Zealand weather and meets the performance standards of AAMA2603 and AS3715. Should your Roof System be more susceptible to salt spray conditions, NZ Louvres will offer a Duratec or an equivalent product to suit your location.

For more information and to view our Frequently Asked Questions (FAQ) please head over to www.nzlouvres.co.nz

